

ACP 252

Compact and competent



**maximum
processing width
25 cm**

ACP 200

The evergreen



**maximum
processing width
20 cm**

ACP 252 and ACP 200: The ideal units for each hobby-lab.

The smallest and most compact processor ever!

THERMAPHOT presents the ACP 252, the smallest paper processing machine in the world for paper formats of up to 24 x 30 cm (maximum processing width 25 cm). This small and modern processor has two tanks, a developer bath and a bleach-fix bath.

It is suitable for RA-4 and other RA-4 compatible processes as well as for black-and-white processes.

After the prints leave the bleach-fix bath, they can be easily washed.

Although it only requires 45 x 42 cm in floor space, the print quality offered by this table-top processor satisfies the most ambitious user.

Its technical design sums up the know-how accumulated in several decades of processor manufacturing, yet it is extremely easy to use and virtually maintenance-free.

At temperatures of up to 24 °C, an optional add-on kit allows you to use „ambient temperature chemicals“.

ACP 252 - Technical data:

Length:	42 cm
Width:	45 cm
Height:	28 cm
Weight (empty):	approx. 16 kg
Entrance speed:	33 cm/min (RA-4) 45 cm/min (RA-4)
Power supply:	230V/240V, 50 Hz 110V/115V, 60 Hz
Max. power consumption:	550 W

ACP 252 - Capacity (RA-4):

Format (cm)	Prints per hour
9 x 13	260
13 x 18	130
18 x 24	100
24 x 30	65

Tank volume: approx. 2 l

The ideal partner for amateur photo labs

The ACP 200 is a paper processing machine for formats of up to 20 x 25 cm. It develops and fixes black-and-white and colour prints automatically and in one process.

One of the main advantages of this machine is its ease of use. It does not require a water supply, and thanks to its small dimensions it can be set up in any amateur lab.

It is suitable for RA-4 and compatible processes as well as to black-and-white paper suitable for machine processing.

The transport system of the machine allows processing times of 45, 120 and 210 seconds. An additional kit allows processing times of 30, 90 and 150 seconds.

The special design of the transport system ensures that between the developer and the fix bath the paper is optimally squeezed, making an additional stop bath unnecessary.

As soon as the exposed paper is introduced into the machine, its cover can be closed. The development process being thus protected from light, you can continue working in full daylight.

ACP 200 - Capacity (RA-4):

Format (cm)	Prints per hour
9 x 13	150
10 x 15	150
13 x 18	110
18 x 24	65
20 x 25	65

Tank volume: approx. 2,5 l

Overview of products

Technical data at a glance: THERMAPHOT paper processors

Product range	ACP 505	ACP 502	HSD 502	ACP 404	ACP 404 BW
Maximum paper format (cm)	50 x 70	50 x 70	50 x 70	40 x 50	40 x 50
Minimum paper format (cm)	9 x 13	9 x 13	9 x 13	9 x 13	9 x 13
Number of tanks	5	2	1+1	4	4
Tank volume (liter/tank)	approx. 5,5	approx. 5,5	approx. 1+5,5	approx. 4,5	approx. 4,5
Dimensions (L x W x H in cm)	approx. 95 x 85 x 45	approx. 62 x 78 x 41	approx. 30 x 78 x 43	approx. 85 x 75 x 45	approx. 85 x 75 x 45
Floor space (L x W in cm)	approx. 88 x 69	approx. 52 x 66	approx. 22 x 66	approx. 78 x 59	approx. 78 x 59
Weight in Kg (empty)	approx. 95	approx. 46	approx. 28	approx. 69	approx. 69
Entrance speed (cm/min.)	10 - 70	10 - 70	same as ACP 502	10 - 70	10 - 70
Processing time range (sec.)	32 - 210	32 - 210	-	32 - 210	32 - 210
Processing temperature range (°C)	28 - 45	28 - 45	-	28 - 45	28 - 45
Total processing time (min:sec.)	4:15 with RA-4	1:35 with RA-4 3:05 with HSD	1:30 with RA-4	3:25 with RA-4	2:30 with BW
Replenishment	automatic	manual optional: automatic	-	manual optional: automatic	manual optional: automatic
Drying	yes infrared tube	no yes with HSD 502	yes infrared tube	yes infrared tube	yes infrared tube
Water consumption (l/min.)	1,4	-	3	1,9	1,9
Capacity in prints/hour format (cm)/approx. qty. (RA-4)	9 x 13 / 760 13 x 18 / 410 20 x 25 / 250 30 x 40 / 85 40 x 50 / 64 50 x 60 / 42	9 x 13 / 760 13 x 18 / 410 20 x 25 / 250 30 x 40 / 85 40 x 50 / 64 50 x 60 / 42	same as ACP 502	9 x 13 / 550 13 x 18 / 365 20 x 25 / 200 30 x 40 / 85 40 x 50 / 52	9 x 13 / 720 13 x 18 / 475 20 x 25 / 260 30 x 40 / 110 40 x 50 / 68
Suitable processes	BW; RA-4 and compatible processes	BW; RA-4 and compatible processes	same as ACP 502	BW; RA-4 and compatible processes	BW
Max power consumption (kW)	2,2	0,65	0,9	1,5	1,5
Order no. 230/240V, 50Hz	2502 (Micro/water) 2506 (Micro/Stabi) 2504 (Analog/water) 2508 (Analog/Stabi)	2512 2514 (replenishment)	2516	2404	2402
Order no. 110/115V, 60Hz	2501 (Micro/water) 2505 (Micro/Stabi) 2503 (Analog/water) 2507 (Analog/Stabi)	2511 2513 (replenishment)	2515	2403	2401
Accessories 230/240V, 50Hz		2412 (replenishment kit)		2412 (replenishment kit)	2412 (replenishment kit)
Accessories 110/115V, 60Hz		2411 (replenishment kit)		2411 (replenishment kit)	2411 (replenishment kit)

ACP 305	ACP 302	ACP 252	ACP 200	UCP 403	UWD 402
30 x 40	30 x 40	24 x 30	20 x 25	40 x 50	40 x 50
9 x 13	9 x 13	9 x 13	9 x 13	13 x 18	13 x 18
5	2	2	2	3	2
approx. 3,4 (optional 2,4)	approx. 2,4 (optional 3,4)	approx. 2	approx. 2,5	approx. 2	approx. 4
approx. 84 x 60 x 40	approx. 48 x 54 x 41	approx. 42 x 45 x 28	approx. 62 x 43 x 25	approx. 85 x 60 x 30	approx. 70 x 60 x 30
approx. 78 x 44	approx. 44 x 44	approx. 42 x 45	approx. 52 x 30	approx. 81 x 47	approx. 66 x 47
approx. 59	approx. 29	approx. 16	approx. 13	approx. 31	approx. 32
46 or 65 optional 10 - 70	46 or 65 optional 10 - 70	33 or 45	28, 11 or 6 optional: 42, 14, 8	6 - 53	same as UCP 403
32 or 45 optional 32 - 210	32 or 45 optional 32 - 210	32 or 45	45, 120 or 210 optional: 30, 90, 150	20 to 180	-
28 - 45	28 - 45	28 - 45	28 - 45	30 - 42	30 - 42
4:15 with RA-4	1:30 with RA-4	1:30 with RA-4	1:30 with RA-4	6:00 with P30P	3:00 with P30P
manual optional: automatic	manual optional: automatic	manual	manual	not required	not required
yes infrared tube	no	no	no	no yes with UWD 402	hot air
1,4	-	-	-	-	-
9 x 13 / 540 13 x 18 / 180 20 x 25 / 90 30 x 40 / 55	9 x 13 / 540 13 x 18 / 180 20 x 25 / 90 30 x 40 / 55	9 x 13 / 260 13 x 18 / 130 18 x 24 / 100 24 x 30 / 65	9 x 13 / 150 13 x 18 / 110 18 x 24 / 65 20 x 25 / 65		
BW; RA-4 and compatible processes	BW; RA-4 and compatible processes	BW; RA-4 and compatible processes	BW; RA-4 and compatible processes	P30P/XP30 P22/P222 P5 BW; RA-4 and compatible processes	same as UCP 403
1,4	0,5	0,55	0,3	0,5	1,7 (UCP+UWD)
2604 (BWD) 2606 (BWDVDR) 2608 (BSDVDR)	2302 2304 (Vario) 2312 (Vario/ replenishment)	0202	0402	6102	6202
2603 (BWD) 2605 (BWDVDR) 2607 (BSDVDR)	2301 2303 (Vario) 2311 (Vario/ replenishment)	0201	0401	6101	6201
2612 (Vario Kit) 2412 (replenishment kit)	2306 (Vario Kit) 2307 (Kit 3,4 l > 3,4 l)		04710 (High Speed Kit for BW)		
2611 (Vario Kit) 2411 (replenishment kit)	2305 (Vario Kit) 2308 (Kit 3,4 l > 2,4 l)		04710 (High Speed Kit for BW)		

THERMAPHOT products are being constantly developed to the latest state of the art. They are therefore subject to modifications without notice. As of: September 1998